BATTERY DATA SHEET







MF MAINTENANCE FREE		
BATTERY	REF BT12	A-BS
		10
Bit Dial Dial <thdial< th=""> Dial Dial D</thdial<>		10.5Ah CAPACITY - Ah (20Hr)
		10Ah CAPACITY - Ah (10Hr)
TECHNOLOGY AGM construction (absorbed acid)		IMENSIONS
 AGM construction (absorbed acid) VRLA battery (Valve Regulated Lead Acid) Supplied with a separate acid pack 	Length (A) : Width (B) : Container height :	88±2mm 105±2mm
Homologated by OEM FEATURES	Total height (C) :	105±2mm
 Upright installation only Maintenance free (no water refilling) 		
 Sealed after filling, no gas emission through venting hole (under normal operation) 		
 High power Does not need to be recharged while stocked Suitable for cold weather 		(C)
 Reduction of plate sulfation Higher life cycle (up to three times longer than 	88mm (B)	
conventional batteries)Longer voltage hold		150mm (A)
UPGRADE FOR	13.2-	ERMINALS
-	ł (
WEIGHT Battery (with acid) : Application of the second s	pprox 3.32kg	
MOUNTING ANGLE	FRONT	SIDE
90° 25° 25° 20° 0° 10° 90° Medium inclinaison	90° TOP	\$6. ⁴
f 🛛 🗅 🖿 BS BATTERY	www.bs-battery.com	sales@bs-battery.com