




Kraftfahrt-Bundesamt

DE-24932 Flensburg



MITTEILUNG

ausgestellt von:

Kraftfahrt-Bundesamt

über die Erteilung einer Genehmigung für einen Schutzhelmtyp mit einem Visiertyp(en) nach der Regelung Nr. 22 einschließlich Änderung Nr. 05 Ergänzung 03

COMMUNICATION

issued by:

Kraftfahrt-Bundesamt

concerning the granting of an approval of a type of protective helmet with one visor type(s) pursuant to Regulation No. 22 including amendment No. 05 supplement 03

Genehmigungsnummer: **E1*22R05/03*300832*00**

Approval number:

1. Fabrik- oder Handelsmarke:
Trade name or mark:
YOHE, NOX, MT, IXS, CGM, BiLT, ONEAL, LAZER, LZR, SPYDER, V, SPIRIT, TECH-X2, RODA, SPEEDS, BILMOLA, Y, RYMIC, HELD, GEON, DUCHINNI, AXXiS, RAPIDO, CASTLE, CASTLEX, RJAYS, TECH-X2, AR1, RIDER, MOX, SHAFT, FTS, MASS, BLACK, RYNOX, PUNTO EXTREMO, ACERBIS, SPY• CGTX, Vinz & Vinz Helmets, ZORAX, SIMPSON, PERMIER
2. Typ:
Type:
910SV
3. Größen:
Sizes:
XS(53/54), S(55/56), M(57/58), L(59/60), XL(61/62), XXL(63/64), XXXL(65/66)
4. Name des Herstellers:
Manufacturer's name:
**Foshan City Nanhai Yongheng Helmet Manufacturing Co. Ltd.
CN-Jiujiang Town, Nanhai, Foshan City**
5. Anschrift:
Address:
**Siehe Punkt 4.
See item 4.**



Kraftfahrt-Bundesamt

DE-24932 Flensburg

2

Genehmigungsnummer: **E1*22R05/03*300832*00**

Approval Number:

6. Name des Vertreters des Herstellers (gegebenenfalls):
Name of manufacturer's representative (if any):
Entfällt
Not applicable
7. Anschrift:
Address:
Siehe Punkt 6.
See item 6.
8. Kurze Beschreibung des Helms:
Brief description of helmet:
Siehe Anlagen
See enclosures
9. **Helm mit schützendem Kinnbügel (P)**
Helmet with protective lower face cover (P)
10. Visiertyp oder Visiertypen:
Type of visor or visors:
101 Visor
E1 22R 05300787
11. Kurze Beschreibung des Visiers oder der Visiere:
Brief description of visor(s):
Siehe Anlagen
See enclosures
12. Zur Genehmigung vorgelegt am:
Submitted for approval on:
22.10.2020
13. Technischer Dienst, der die Prüfungen für die Genehmigungen durchführt:
Technical service responsible for conducting approval tests:
SGS-TÜV Saar GmbH
DE-81379 München
14. Datum des Gutachtens des Technischen Dienstes:
Date of report issued by that service:
19.10.2020
15. Nummer des Gutachtens des Technischen Dienstes:
Number of report issued by that service:
HOM ECN T20/103-00



Kraftfahrt-Bundesamt

DE-24932 Flensburg

3

Genehmigungsnummer: **E1*22R05/03*300832*00**

Approval Number:

16. Bemerkung(en):
Remark(s):
Handelsbezeichnung(en)/ General commercial description(s):
CHARGER, FURY
17. Die Genehmigung wird **erteilt**
Approval is **granted**
18. Ort: **DE-24932 Flensburg**
Place:
19. Datum: **24.11.2020**
Date:
20. Unterschrift: **Im Auftrag**
Signature:


(D. Stieglitz)



21. Folgende mit der oben erwähnten Genehmigungsnummer versehene Dokumente sind auf Anforderung erhältlich:
The following documents, bearing the approval number shown above, are available on request:

Anlagen:
Enclosures:
Gemäß Inhaltsverzeichnis
According to index



Kraftfahrt-Bundesamt

DE-24932 Flensburg

Zu: E1*22R05/03*300832*00

To:

Erklärung über die Einhaltung der Anforderungen hinsichtlich der Übereinstimmung der Produktion gemäß dem Übereinkommen von 1958
Statement of compliance with the conformity of the production requirements of the 1958 Agreement

1. Name des Herstellers:
Manufacturer's name:
Foshan City Nanhai Yongheng Helmet Manufacturing Co. Ltd.
CN-Jiujiang Town, Nanhai, Foshan City

2. Datum der Anfangsbewertung:
Date of the initial assessment:
26.01.2010

3. Datum aller durchgeführten Überwachungstätigkeiten:
Date of any surveillance activities:

Aktenzeichen Register number	Datum der Begehung Date of inspection	Genehmigungsnummer Approval number
CoP-Q: Q-500614	22.11.2016	
CoP-P: Entfällt		
Not applicable		



Kraftfahrt-Bundesamt

DE-24932 Flensburg

Zu: **E1*22R05/03*300832*00**

To:

Inhaltsverzeichnis zu den Beschreibungsunterlagen Index to the information package

Ausgabedatum: **24.11.2020** Letztes Änderungsdatum: **--**
Date of issue: Last date of amendment:

Nebenbestimmungen und Rechtsbehelfsbelehrung
Collateral clauses and instruction on right to appeal

Prüfbericht(e) Nr.: Datum:
Test report(s) No.: Date:
HOM ECN T20/103-00 **19.10.2020**

Beschreibungsbogen Nr.: Datum:
Information document No.: Date:
R22-910SV-00 **16.10.2020**

Liste der Änderungen: Datum:
List of modifications: Date:
Entfällt
Not applicable

R22 E1*22R05/03*300832*00



Kraftfahrt-Bundesamt

DE-24932 Flensburg

Nummer der Genehmigung: **E1*22R05/03*300832*00**

- Anlage -

Nebenbestimmungen und Rechtsbehelfsbelehrung

Nebenbestimmungen

Jede Einrichtung, die dem genehmigten Typ entspricht, ist gemäß der angewendeten Vorschrift zu kennzeichnen.

Die Einzelerzeugnisse der reihenweisen Fertigung müssen mit den Genehmigungsunterlagen genau übereinstimmen. Änderungen an den Einzelerzeugnissen sind nur mit ausdrücklicher Zustimmung des Kraftfahrt-Bundesamtes gestattet.

Änderungen der Firmenbezeichnung, der Anschrift und der Fertigungsstätten sowie eines bei der Erteilung der Genehmigung benannten Zustellungsbevollmächtigten oder bevollmächtigten Vertreters sind dem Kraftfahrt-Bundesamt unverzüglich mitzuteilen.

Verstöße gegen diese Bestimmungen können zum Widerruf der Genehmigung führen und können überdies strafrechtlich verfolgt werden.

Die Genehmigung erlischt, wenn sie zurückgegeben oder entzogen wird, oder der genehmigte Typ den Rechtsvorschriften nicht mehr entspricht. Der Widerruf kann ausgesprochen werden, wenn die für die Erteilung und den Bestand der Genehmigung geforderten Voraussetzungen nicht mehr bestehen, wenn der Genehmigungsinhaber gegen die mit der Genehmigung verbundenen Pflichten - auch soweit sie sich aus den zu dieser Genehmigung zugeordneten besonderen Auflagen ergeben - verstößt oder wenn sich herausstellt, dass der genehmigte Typ den Erfordernissen der Verkehrssicherheit oder des Umweltschutzes nicht entspricht.

Das Kraftfahrt-Bundesamt kann jederzeit die ordnungsgemäße Ausübung der durch diese Genehmigung verliehenen Befugnisse, insbesondere die genehmigungsgerechte Fertigung sowie die Maßnahmen zur Übereinstimmung der Produktion, nachprüfen. Es kann zu diesem Zweck Proben entnehmen oder entnehmen lassen. Dem Kraftfahrt-Bundesamt und/oder seinen Beauftragten ist ungehinderter Zutritt zu Produktions- und Lagerstätten zu gewähren.

Die mit der Erteilung der Genehmigung verliehenen Befugnisse sind nicht übertragbar. Schutzrechte Dritter werden durch diese Genehmigung nicht berührt.

Rechtsbehelfsbelehrung

Gegen diese Genehmigung kann innerhalb eines Monats nach Bekanntgabe Widerspruch erhoben werden. Der Widerspruch ist beim **Kraftfahrt-Bundesamt, Fördestraße 16, DE-24944 Flensburg**, schriftlich oder zur Niederschrift einzulegen.



Kraftfahrt-Bundesamt

DE-24932 Flensburg

2

Approval No.: **E1*22R05/03*300832*00**

- Attachment -

Collateral clauses and instruction on right to appeal

Collateral clauses

All equipment which corresponds to the approved type is to be identified according to the applied regulation.

The individual production of serial fabrication must be in exact accordance with the approval documents. Changes in the individual production are only allowed with express consent of the Kraftfahrt-Bundesamt.

Changes in the name of the company, the address and the manufacturing plant as well as one of the parties given the authority to delivery or authorised representative named when the approval was granted is to be immediately disclosed to the Kraftfahrt-Bundesamt.

Breach of this regulation can lead to recall of the approval and moreover can be legally prosecuted.

The approval expires if it is returned or withdrawn or if the type approved no longer complies with the legal requirements. The revocation can be made if the demanded requirements for issuance and the continuance of the approval no longer exist, if the holder of the approval violates the duties involved in the approval, also to the extent that they result from the assigned conditions to this approval, or if it is determined that the approved type does not comply with the requirements of traffic safety or environmental protection.

The Kraftfahrt-Bundesamt may check the proper exercise of the conferred authority taken from this approval at any time. In particular this means the compliant production as well as the measures for conformity of production. For this purpose samples can be taken or have taken. The employees or the representatives of the Kraftfahrt-Bundesamt may get unhindered access to the production and storage facilities.

The conferred authority contained with issuance of this approval is not transferable. Trade mark rights of third parties are not affected with this approval.

Instruction on right to appeal

This approval can be appealed within one month after notification. The appeal is to be filed in writing or as a transcript at the **Kraftfahrt-Bundesamt, Fördestraße 16, DE-24944 Flensburg.**

Technical Report

V00

Test standard:
ECE Regulation No. 22

Level of amendment:
Supplement 3 to the 05 series of amendments

Title:
Protective helmets and their visors

Manufacturer:
FOSHAN CITY NANHAI YONGHENG HELMET MANUFACTURING CO., LTD.

Type:
910SV

Subject of testing:
Component

0 General

0.1	Make (trade name of manufacturer):	YOHE, NOX, MT, IXS, CGM, BiLT, ONEAL, LAZER, LZR, SPYDER, V, SPIRIT, TECH-X2, RODA, SPEEDS, BILMOLA, Y, RYMIC, HELD, GEON, DUCHINNI, AXXiS, RAPIDO, CASTLE, CASTLEX, RJAYS, TECH-X2, AR1, RIDER, MOX, SHAFT, FTS, MASS, BLACK, RYNOX, PUNTO EXTREMO, ACERBIS, SPY , GTX, Vinz & Vinz Helmets, ZORAX, SIMPSON, PERMIER
0.2	Type:	910SV
0.2.1	Commercial description:	CHARGER, FURY
0.3	Means of identification of type, if marked on the vehicle:	n.a.
0.3.1	Location of that marking:	n.a.
0.4	Category of vehicle:	n.a.
0.5	Manufacturer's name and address:	FOSHAN CITY NANHAI YONGHENG HELMET MANUFACTURING CO., LTD. Yannan Industrial Area, Longgao Road, Jiujiang, Foshan City, Guangdong Province, China
0.8	Address of assembly plant:	FOSHAN CITY NANHAI YONGHENG HELMET MANUFACTURING CO., LTD. Yannan Industrial Area, Longgao Road, Jiujiang, Foshan City, Guangdong Province, China
0.9	Name and address of representative:	n.a.
	Location of the ECE approval mark:	refer to information document

R22 E1*22R05/03*300832*00

1 Test record

See appendix

2 Attachments

2.1 List of modifications:

2.2 Information folder:

No.: R22-910SV-00

Date of issue: 16.10.2020

3 Statement of conformity

The information folder as mentioned under no. 2.2 and the type described therein are in compliance with the test standard mentioned above.

With regard to the required level of performance to be achieved, the test specimen were representative for the type to be approved.

The tests were carried out in accordance to the relevant requirements of the

EN ISO/IEC 17025:2005 EN ISO/IEC 17020:2012

**Test Laboratory
 SGS-TÜV Saar GmbH**

notified by

Kraftfahrt-Bundesamt (KBA),
 Federal Republic of Germany

National Standards
 Authority of Ireland (NSAI)

Rijksdienst voor het Wegverkeer
 (RDW),
 The Netherlands

No. KBA - P 00084 – 10

No. 101

No. 99050064 00

Responsible expert

Signature

Lell Wu

Oct 19, 2020



Conformity check

Signature

Perry Li



This Technical Report shall be reproduced and published in full only and by the client only. It shall be reproduced partially with the written permission of the Test Laboratory only.

This document is issued by the Company subject to its General Conditions of Service (www.sgsgroup.de/agb). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. This document is an original. If the document is submitted digitally, it is to be treated as an original within the meaning of UCP 600. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Test record

1 Test object and measuring equipment

1.1 Test object

- Protective helmet (without visor)
- Protective helmet (with visor)
- Visor

1.1.1 Protective Helmet

Type: 910SV
 Sizes: XS(53/54), S(55/56), M(57/58), L(59/60), XL(61/62) , XXL(63/64), XXXL(65/66)
 Lower face cover: Without lower face cover (J)
 Protective (P)
 Non protective (NP)

1.1.2 Helmet visor

Visor type: 101 Visor
 Refer to approval no.: E1 22R 05300787

1.1.3 Sun shade

The helmet is equipped with a swivel-mounted sun shade, which may only be used in combination with the visor in closed position according to the user manual

- On the inner side of the visor
- On the outer side of the visor
- Not applicable

1.1.4 Remarks:

n.a.

1.2 Equipments for measuring and testing:

1.2.1 Test equipment:

The equipment and the test facilities on which the tests were carried out fulfilled the requirements of the ECE Regulation 22.05

1.2.2 Measurement procedure:

according to ECE Regulation No. 22.05

2 Test Results

2.1 Protective helmet

2.1.1 Marking (clause 4.1.1, 4.4)

All required information, in accordance with the ECE R22.05, is given by the labels


- fulfilled
- Not fulfilled
- n.a.

2.1.2 Basic construction (clause 6.1)

Shell + Protective padding + Retention system

- fulfilled
- Not fulfilled
- n.a.

2.1.3 If fitted with non protective lower face cover (clause 6.2)

- Marked
"Does not protect chin from impacts"
- Marked
with symbol 
- n.a.

2.1.4 Extent of the protection (clauses 6.4, 6.5)

The shell and the protective padding cover all areas as required

- fulfilled
- Not fulfilled
- n.a.

2.1.5 Projections / irregularities / sharp edges
(clauses 6.6 to 6.9)

All external projections other than press-fasteners are smooth and adequately faired, all external projections which are not more than 2 mm above the outer surface of the shell, have a radius of more than 1 mm, all external projections which are more than 2 mm above the outer surface of the shell have a radius of more than 2 mm.

All projections or irregularities in the outer surface of the shell which are higher than 2 mm, fulfill the requirements after the shear assessment test. The outer surface of the helmet fulfills the requirements after the friction assessment test.

There are no inward-facing sharp edges on the inside of the helmet; rigid, projecting internal parts are covered with padding so that any stresses transmitted to the head are not highly concentrated.

- fulfilled
- Not fulfilled
- n.a.

2.1.6 Test method for projections and surface friction

- Procedure A (7.4.1)
- Procedure B (7.4.2)

Helmet No.	Helmet Size (cm)	Condition	Projections	Friction
M-3	57/58	Solvent plus ambient temperature and hygrometry conditioning	Pass	Pass

2.1.7 Peripheral vision (clause 6.14)

Horizontal ($\geq 105^\circ$):

<input checked="" type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input type="checkbox"/>	n.a.

Upwards ($\geq 7^\circ$):

<input checked="" type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input type="checkbox"/>	n.a.

Downwards ($\geq 45^\circ$):

<input checked="" type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input type="checkbox"/>	n.a.

2.1.8 Conspicuity marking
(clause 6.16)

<input type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input checked="" type="checkbox"/>	n.a.

2.1.9 Impact-absorption tests
(clause 7.3)

x	fulfilled
	Not fulfilled
	n.a.

Size: 61/62 cm

Test Head Form: O (62 cm)

Helmet No.	Condition	Test anvil	Test site	Velocity (m/s)	Peak 'G ≤275g	HIC ≤2400
XL-1	Solvent plus ambient temperature and hygrometry conditioning	Kerbstone	B	7.55	155.0	1078
		Kerbstone	X	7.58	178.0	1218
		Flat	P	7.55	191.5	1883
		Flat	R	7.56	159.4	1298
XL-2	Solvent plus ambient temperature and hygrometry conditioning	Flat	B	7.53	170.2	1426
		Flat	X	7.54	241.4	1852
		Kerbstone	P	7.52	153.1	1160
		Kerbstone	R	7.55	121.8	806
XL-3	Solvent plus heat conditioning	Kerbstone	B	7.52	250.4	1161
		Kerbstone	X	7.57	200.4	1322
		Kerbstone	P	7.59	156.3	1089
		Kerbstone	R	7.53	110.0	867
XL-4	Solvent plus low temperature conditioning	Flat	B	7.53	167.5	1270
		Flat	X	7.54	250.4	1958
		Flat	P	7.58	210.5	2106
		Flat	R	7.59	168.3	1167
		Flat	S	5.57	233.2	1043
XL-5	Solvent plus ultra-violet radiation conditioning and moisture conditioning	Kerbstone	B	7.53	154.0	1013
		Flat	X	7.50	216.1	1381
		Flat	P	7.55	202.4	2008
		Kerbstone	R	7.56	168.7	1249

R22 E1*22R05/03*300832*00

Size: 53/54 cm

Test Head Form: E (54 cm)

Helmet No.	Condition	Test anvil	Test site	Velocity (m/s)	Peak 'G ≤275g	HIC ≤2400
XS-1	Solvent plus heat conditioning	Kerbstone	B	7.53	158.5	1100
		Kerbstone	X	7.56	266.9	2043
		Kerbstone	P	7.54	139.9	866
		Kerbstone	R	7.55	107.8	481
XS-2	Solvent plus low temperature conditioning	Flat	B	7.56	180.7	1428
		Flat	X	7.57	256.7	2253
		Flat	P	7.55	183.9	1815
		Flat	R	7.58	154.1	828
		Flat	S	5.57	181.6	830

Size: 57/58 cm

Test Head Form: J (57 cm)


Helmet No.	Condition	Test anvil	Test site	Velocity (m/s)	Peak 'G ≤275g	HIC ≤2400
M-1	Solvent plus heat conditioning	Kerbstone	B	7.54	153.7	1084
		Kerbstone	X	7.60	207.7	1364
		Kerbstone	P	7.54	157.0	1240
		Kerbstone	R	7.56	126.3	1076
M-2	Solvent plus low temperature conditioning	Flat	B	7.56	215.0	1886
		Flat	X	7.59	257.2	2241
		Flat	P	7.62	216.1	2234
		Flat	R	7.57	185.8	1473
		Flat	S	5.55	170.4	676

Size: 59/60 cm

Test Head Form: M (60 cm)

Helmet No.	Condition	Test anvil	Test site	Velocity (m/s)	Peak 'G ≤275g	HIC ≤2400
L-1	Solvent plus heat conditioning	Kerbstone	B	7.56	129.4	964
		Kerbstone	X	7.56	205.9	1431
		Kerbstone	P	7.60	193.9	1391
		Kerbstone	R	7.58	139.5	1196
L-2	Solvent plus low temperature conditioning	Flat	B	7.57	173.8	1455
		Flat	X	7.61	248.2	2047
		Flat	P	7.55	219.6	2192
		Flat	R	7.58	159.4	1464
		Flat	S	5.58	147.1	657

2.1.10 Rigidity test (clause 7.5)



- fulfilled
- Not fulfilled
- n.a.

Helmet No.	Size	Condition	Direction	Max. deformation (≤ 40 mm)	Residual deformation (≤ 15 mm)
XL-6	61/62	Solvent plus ambient temperature and hygrometry conditioning	Longitudinal axis	15.8	3.0
XL-7	61/62	Solvent plus ambient temperature and hygrometry conditioning	Transverse axis	12.0	2.5

2.2 Retention system

2.2.1 The retention system is protected from abrasion

- fulfilled
- Not fulfilled
- n.a.

2.2.2 Chin strap (clause 6.11.1, 6.11.2)

The width of the chin strap is more than 20 mm under load of 150 N and it doesn't include a chin-cup.

- fulfilled
- Not fulfilled
- n.a.

2.2.3 Adjustment device (clause 6.11.3)

The retention system includes a device to adjust and maintain tension.

- fulfilled
- Not fulfilled
- n.a.

2.2.4 Fastening devices
(clauses 6.11.4 to 6.11.9)

The requirements for fastening devices and release mechanisms are in accordance to the requirements of the test standard.

- fulfilled
- Not fulfilled
- n.a.

2.2.5 Retention system dynamic test
(clause 7.6)

- fulfilled
- Not fulfilled
- n.a.

Helmet No.	Helmet Size (cm)	Condition	Dynamic displacement (≤ 35 mm)	Residual displacement (≤ 25 mm)
XS-3 With type 1 retention system	53/54	Solvent plus ambient temperature and hygrometry conditioning	27.2	14.1
XS-4 With type 2 retention system	53/54	Solvent plus ambient temperature and hygrometry conditioning	32.2	16.7
XS-5 With type 3 retention system	53/54	Solvent plus ambient temperature and hygrometry conditioning	32.5	15.5
XS-6 With type 4 retention system	53/54	Solvent plus ambient temperature and hygrometry conditioning	29.3	13.3

2.2.6 Retention (detaching) test (clause 7.7) fulfilled
 Not fulfilled
 n.a.

Helmet No.	Helmet Size (cm)	Condition	Movement of the reference line ($\leq 30^\circ$)
XS-3 With type 1 retention system	53/54	Solvent plus ambient temperature and hygrometry conditioning	23°
XS-4 With type 2 retention system	53/54	Solvent plus ambient temperature and hygrometry conditioning	24°
XS-5 With type 3 retention system	53/54	Solvent plus ambient temperature and hygrometry conditioning	25°
XS-6 With type 4 retention system	53/54	Solvent plus ambient temperature and hygrometry conditioning	25°

2.2.7 Micro-slip test of the chin strap (clause 7.9) fulfilled
 Not fulfilled
 n.a.

Slippage of chin strap: ($\leq 10\text{mm}$): <10 mm

2.2.8 Chin strap, resistance to abrasion test (clause 7.10) fulfilled
 Not fulfilled
 n.a.

2.2.8.1 Chin strap, withstand a tension of 3 kN (clause 7.10.5) fulfilled
 Not fulfilled
 n.a.

2.2.9 Retention systems relying on quick-release mechanisms (clause 7.11)

R22 E1*22R05/03*300832*00

2.2.9.1 Inadvertent release by pressure
(clause 7.11.1)

- fulfilled
- Not fulfilled
- n.a.

2.2.9.2 Ease of release
(clause 7.11.2)

- fulfilled
- Not fulfilled
- n.a.

2.2.9.3 Durability of quick-release
mechanisms (clause 7.11.3)

- fulfilled
- Not fulfilled
- n.a.

2.3 Visor

- n.a. (no visor)
- n.a. (visor separately approved)

Refer to approval no.: E1 22R 05300787

2.4 Information for wearers
(clauses 14.1 to 14.6)

2.4.1 Every protective helmet placed on the market shall bear a clearly visible label with the following inscription in the national language, or at least one of the national languages, of the country of destination:

- fulfilled
- Not fulfilled
- n.a.

"For adequate protection, this helmet must fit closely and be securely attached. Any helmet that has sustained a violent impact should be replaced"

and, if fitted with a non protective lower face cover:

- fulfilled
- Not fulfilled
- n.a.

"Does not protect chin from impacts"

together with the symbol indicating the unsuitability of the lower face cover to offer any protection against impacts to the chin

2.4.2 and, if hydrocarbons, cleaning fluids, paints, transfers or other extraneous additions affect the shell material adversely

<input checked="" type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input type="checkbox"/>	n.a.

“Warning’ - Do not apply paint, stickers, petrol or other solvents to this helmet”

2.4.3 Every protective helmet shall be clearly marked with its size and its maximum weight, to the nearest 50 grammes, as placed on the market. The maximum weight quoted should include all the accessories that are supplied with the helmets, within the packaging, as it is placed on the market, whether or not those accessories have actually been fitted to the helmet.

<input checked="" type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input type="checkbox"/>	n.a.

2.4.4 Every protective helmet offered for sale shall bear a label showing the type or types of visor that have been approved at the manufacturer's request.

<input checked="" type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input type="checkbox"/>	n.a.

2.4.5 Every visor offered for sale shall bear a label showing the types of protective helmet for which it has been approved

<input checked="" type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input type="checkbox"/>	n.a.

2.4.6 Every visor placed on the market with a protective helmet shall be accompanied by information in the national language, or in at least one of the national languages, of the country of destination. This information shall contain:

2.4.6.1 General Instruction for Storage and Care

<input checked="" type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input type="checkbox"/>	n.a.

R22 E1*22R05/03*300832*00

2.4.6.2 Specific instructions for cleaning and their notice of use. These instructions shall include a warning regarding the dangers of using unsuitable agents for cleaning (such as solvents), especially if abrasion resistant coatings are to be preserved.

<input checked="" type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input type="checkbox"/>	n.a.

2.4.6.3 Advice as to the suitability of the visor for use in conditions of poor visibility and during the hours of darkness. The following warning shall be included:

Visors with the marking indicating "daytime use only" are not suitable for use during the hours of darkness or in conditions of poor visibility.

<input checked="" type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input type="checkbox"/>	n.a.

2.4.6.4 If appropriate, the following warning shall also be included
 The fastening of this visor is such that it will not be possible to remove it instantly from the line of sight with one hand should an emergency (such as headlamp glare or misting) occur.

<input type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input checked="" type="checkbox"/>	n.a.

2.4.6.5 If the visor is MIST RETARDANT approved it may be indicated

<input type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input checked="" type="checkbox"/>	n.a.

2.4.6.6 Instructions regarding the detention of obsolescence

<input checked="" type="checkbox"/>	fulfilled
<input type="checkbox"/>	Not fulfilled
<input type="checkbox"/>	n.a.

3 Other information

Place of testing: SGS CSTC Guangzhou, P.R. China

Date of testing: From 30.09.2020 to 13.10.2020

4 Remarks: ---



List of modifications

- | | | |
|---|------------------|------|
| 1 | Correction of: | n.a. |
| 2 | Modification of: | n.a. |
| 3 | Addition of: | n.a. |
| 4 | Deletion of: | n.a. |